

DECLARATION OF PERFORMANCE No.: 09/R/2023

1	Unique identification code of the product-type:	Matizol Color Deck														
2	Intended use:	Coloured, step-steady, non-slip, water-based, elastomeric membrane														
3	Manufacturer:	Selena FM S.A. Ul. Legnicka 48A 54-202 Wrocław Poland www.ce.selena.com														
4	Authorised representative:	Not applicable														
5	System/s of AVCP:	System 4														
6a	Harmonised standard: Notified body/ies:	UNI EN 1504-2 Concrete surface protection systems (MC-IR)														
6b	European Assessment Document:	Not applicable														
	European Technical Assessment:	Not applicable														
	Technical Assessment Body: Notified body:	Not applicable														
7	Declared performances:															
	<table><tr><td>Essential Characteristics</td><td>Performance</td></tr><tr><td>Water vapour permeability</td><td>$5\text{m} \leq s_d \leq 50\text{ m}$</td></tr><tr><td>Capillary absorption</td><td>$W < 0,1\text{ kg/m}^2 \cdot \text{h}^{0,5}$</td></tr><tr><td>Adhesion strength (horizontal with traffic)</td><td>$\geq 1,5\text{ N/mm}^2$</td></tr><tr><td>Thermal shock cycles (horizontal with traffic)</td><td>$\geq 1,5\text{ N/mm}^2$</td></tr><tr><td>Fire reaction</td><td>F</td></tr><tr><td>Dangerous Substances Emission</td><td>See MSDS</td></tr></table>		Essential Characteristics	Performance	Water vapour permeability	$5\text{m} \leq s_d \leq 50\text{ m}$	Capillary absorption	$W < 0,1\text{ kg/m}^2 \cdot \text{h}^{0,5}$	Adhesion strength (horizontal with traffic)	$\geq 1,5\text{ N/mm}^2$	Thermal shock cycles (horizontal with traffic)	$\geq 1,5\text{ N/mm}^2$	Fire reaction	F	Dangerous Substances Emission	See MSDS
Essential Characteristics	Performance															
Water vapour permeability	$5\text{m} \leq s_d \leq 50\text{ m}$															
Capillary absorption	$W < 0,1\text{ kg/m}^2 \cdot \text{h}^{0,5}$															
Adhesion strength (horizontal with traffic)	$\geq 1,5\text{ N/mm}^2$															
Thermal shock cycles (horizontal with traffic)	$\geq 1,5\text{ N/mm}^2$															
Fire reaction	F															
Dangerous Substances Emission	See MSDS															
8	Appropriate Technical Documentation and/or Specific Technical Documentation:	-														

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wrocław

18.07.2023

Renata Lechonievicz



Test and Certification Leader