

DECLARATION OF PERFORMANCE No.: **10/R/2023**

1	Unique identification code of the product-type:	Matizol Color Roof														
2	Intended use:	Water-based elastomeric waterproofing coloured liquid membrane														
3	Manufacturer:	Selena FM S.A. Ul. Legnicka 48A 54-202 Wrocław Poland www.ce.selena.com														
4	Authorised representative:	Not applicable														
5	System/s of AVCP:	System 4														
6a	Harmonised standard: Notified body/ies:	UNI EN 1504-2 Concrete surface protection systems (MC-IR)														
6b	European Assessment Document:	Not applicable														
	European Technical Assessment:	Not applicable														
	Technical Assessment Body: Notified body:	Not applicable														
7	Declared performances:	<table border="1"> <thead> <tr> <th>Essential Characteristics</th> <th>Performance</th> </tr> </thead> <tbody> <tr> <td>Water vapour permeability</td> <td>$5m \leq sd \leq 50 m$</td> </tr> <tr> <td>Capillary absorption</td> <td>$W < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$</td> </tr> <tr> <td>Adhesion strength (horizontal with traffic)</td> <td>$\geq 1,0 \text{ N/mm}^2$</td> </tr> <tr> <td>Thermal shock cycles (horizontal with traffic)</td> <td>$\geq 1,0 \text{ N/mm}^2$</td> </tr> <tr> <td>Fire reaction</td> <td>F</td> </tr> <tr> <td>Dangerous Substances Emission</td> <td>See MSDS</td> </tr> </tbody> </table>	Essential Characteristics	Performance	Water vapour permeability	$5m \leq sd \leq 50 m$	Capillary absorption	$W < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	Adhesion strength (horizontal with traffic)	$\geq 1,0 \text{ N/mm}^2$	Thermal shock cycles (horizontal with traffic)	$\geq 1,0 \text{ N/mm}^2$	Fire reaction	F	Dangerous Substances Emission	See MSDS
Essential Characteristics	Performance															
Water vapour permeability	$5m \leq sd \leq 50 m$															
Capillary absorption	$W < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$															
Adhesion strength (horizontal with traffic)	$\geq 1,0 \text{ N/mm}^2$															
Thermal shock cycles (horizontal with traffic)	$\geq 1,0 \text{ N/mm}^2$															
Fire reaction	F															
Dangerous Substances Emission	See MSDS															
8	Appropriate Technical Documentation and/or Specific Technical Documentation:	-														

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wrocław 18.07.2023

Renata Lechoniewicz



Test and
Certification Leader